



1300 SERIES

Impeccable clarity meets astounding design, for a speaker that's bound to impress every time. It's a perfect fit for multi-room audio, home theater, and beyond.

- **Polypropylene Woofer** – Forward-set for wide dispersion and punchy bass.
- **Adjustable Silk Dome Tweeter** – Direct sound where you want to create more immersive experiences.
- **Ribbed Surround** – Ensures linear cone movement for tighter bass and less distortion.
- **Multiple Grille Options** – Magnetic, one-step paintable grille keeps the speaker out of sight, available in a variety of design options to fit your installation needs.

Model	Placement	Type	Size	Cutout Dimensions	Finished Dimensions (Size with Grille)
ESS-1300T-IC-4	In-Ceiling	Standard	4"	6.2"	7.5"
ESS-1300T-IC-6	In-Ceiling	Standard	6"	8.3"	9.6"
ESS-1300T-IC-8	In-Ceiling	Standard	8"	9.7"	11.0"
ESS-1300T-ICDVC-6	In-Ceiling	DVC	6"	8.3"	9.6"
ESS-1300T-IW-6	In-Wall	Standard	6"	11.7" x 7.6"	13.0" x 8.9"
ESS-1300T-IW-8	In-Wall	Standard	8"	13.7" x 9.0"	15.0" x 10.3"
ESS-1300T-IWDVC-6	In-Wall	DVC	6"	11.7" x 7.6"	13.0" x 8.9"
ESS-1300T-POINT-6	In-Ceiling	Point	6"	9.7"	11"

* In-Wall DVC tweeters are not adjustable

Please contact your custom integrator for speaker availability.



ESS-1300TIC8

Specifications:

- Woofer: 6½" Treated Paper Cone, Nomex Spider & High Temp Voice Coil
- Tweeter: 1/2" Fabric Domes, Neodymium Motor, Ferrofluid Cooled
- Power Handling: 50 Watts RMS, 125 Watt Peak
- Nominal Impedance: 6
- Frequency Response(-6dB): 58Hz - 20KHz
- Sensitivity -2.83 V / 1 Meter: 87
- Adjustments: N/A
- Crossover Frequency: 4.3 kHz
- Connector Type: Gold Plated Push Terminals
- Weight: 2.1 lbs
- Grill Type: Powder Coated Perforated Grill
- Cutout Dimensions: 7.5" diameter
- Mounting Depth: 2.25"
- Finished Dimensions: 8.5" diameter, 3" D